

MOS-3340Y-1210E

LCD Display Port iDoor Module

NEW



Features

- Supports 18/24 or 36/48 -bit LVDS Signal
- Supports 3.3V/5V/12V Power Supply
- Supports Embedded PC ARK-2230L/ARK-6322

Specifications

LCD	48-bit dual channel LVDS up to WUXGA 1280x1024 at 60Hz, support 18-bit/24-bit or 36-bit/48-bit LVDS signal
LCD Connector	DB9 (Backlight) + 26 Pin D SUB (LVDS Signal)
Supply Voltage and Current	Default support +5V ±5%, 2.5A +3.3V/12V support by platform
OS Supported	Windows 7/ 8
Temperature Ranges	Operation: -40 to +85 °C Storage: -40 to +85 °C
Dimensions (L x W x H)	36.50*89.60 *19.4 mm

Ordering Information

Part No.	Product Description
MOS-3340Y-1201E	LVDS module 18/24/36/48 bit, 3.3V/5V/12V LCD
MOS-3340	Support by Project for BIOS Update (TPN, MOQ =30)

Packing List

P/N	Description
-	1x MOS-3340 LVDS I/O Module
1700026696-01	1x LVDS Cable
1700026697-01	1x Inverter Cable
-	1x Quick Start Guide
-	1x CARDBOARD-WARRANTY REV. A2

Dimensions

Unit: mm

