

KONTRON FusionView



A NEW DIMENSION OF VISUALIZATION

- ▶ Intuitive, multi-touch edge to edge frameless front panel
- ▶ Industrial grade - robust, reliable, and maintenance-free
- ▶ Various display dimensions: 12.1" / 15.6" / 18.5" / 21.5"
- ▶ Easy-clean, antiglare and scratch-proof IP65 protected front glass
- ▶ Access control via RFID (optional)

POSSIBILITIES START HERE



kontron

FusionView

A NEW DIMENSION OF VISUALIZATION

Inspired by the stunning design of the FusionClient, Kontron has developed an industrial grade display as an extension to your existing industrial computer portfolio.

Combined with Kontron's FusionClient, KBox and rackmount the FusionView enables intuitive multi-touch access to real-time actionable data, therefore making it the perfect fit for SCADA and Manufacturing Execution Systems (MES), process visualization and other control applications.

All FusionView models feature an easy-clean, antiglare and scratch-proof IP65 protected front glass. Based on the wide display format, FusionView is available in four sizes (12.1", 15.6", 18.5" and 21.5"), which can be operated in both landscape and portrait format.

Display adjustments can be made either through OSD via capacitive buttons, or via software applications ("Soft-OSD").

An RFID reader, which is installed behind the glass, makes it possible to customize different authorization and security levels; thus providing in-depth access control.

► TECHNICAL INFORMATION

DISPLAY SIZE	12.1"	15.6"	18.5"	21.5"
RESOLUTION	1280 x 800	1366 x 768	1366 x 768	1920 x 1080
FORMAT	16:10	16:9	16:9	16:9
BRIGHTNESS (DISPLAY)	400 cd/m ²	400 cd/m ²	400 cd/m ²	300 cd/m ²
LED BACKLIGHT	Life time ≥ 50.000h			
TOUCH SCREEN	Projected capacitive touch (PCAP), multi-touch			
DIMENSIONS (HxWxD)	266 x 328 x 67,6 mm	298 x 414 x 67,6 mm	337 x 480 x 67,6 mm	373 x 545 x 67,6 mm
MOUNTING	Panel mount or VESA			
INTERFACES	DVI-I, DP, USB Type B (Slave)			
WIRELESS INTERFACES	RFID			
POWER SUPPLY	24 VDC (± 25 %)			
EMC	CE: EN 61000-6-2; EN 55022 Class B			
CERTIFICATIONS	CE, designed for UL			
ALTITUDE	Operating: 10000 ft (3.000 m) / Storage: 15000 ft (4.572 m)			
SHOCK ACC. TO EN 60068-2-27	Operating 15 G 11 ms duration (half sine) Storage 30 G 11 ms duration (half sine)			
VIBRATION ACC. TO EN 60068-2-6	Operating 10-500 Hz: 1G/3 axis Storage 10-500 Hz: 2G/3 axis			
OPERATING TEMPERATURE	0 °C to +50 °C			
PROTECTION CLASS	IP65 front, IP20 rear			
HUMIDITY	5 % to 90 % non-condensing			
MTBF	> 50.000h (excluding backlight)			
VERIFIED OS	Windows 7; Windows 10; Linux Embedded			
RoHS COMPLIANT	Yes			

► CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: + 49 821 4086 0
Fax: + 49 821 4086 111
info@kontron.com

NORTH AMERICA

9477 Waples Street
San Diego, CA 92121
USA
Tel.: + 1 888 294 4558
Fax: + 1 858 677 0898
info@us.kontron.com

ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,
Economical & Technological Development Zone,
Beijing, 100176, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn